

High Bay

Double Linear




LED Double Linear High Bay

Part Number	LOT-BAY-180-22	LOT-BAY-240-22	LOT-BAY-300-22	LOT-BAY-360-22	LOT-BAY-480-22
Lumen Output	21,600lm	28,800lm	36,000lm	43,200lm	57,600lm
Wattage	180W	240W	300W	360W	480W
Lumen Efficacy	120lm/W				
CCT	4500~5500K(2500~5500K optional)				

Beam Angle	40°80°(55°130°optional)
Input Voltage	100-277Vac 47-63Hz PF 0.95
IP Rating	IP 65
LED Driver	Meanwell

Certification	UL, CE, PSE, SAA, RoHS
---------------	------------------------

Photometric Diagrams



Detail



LED Technology

The LED Double Linear High Bay can produce the perfect glare-free lighting to places such as workshops, warehouses, shopping malls, garages, lobbies and other similar places. The LED Linear High Bay has an anodized heat sink that has an anti-corrosion capacity and at the same time, allows the Linear II to have an excellent heat dissipation. The LED Linear High Bay has an IP65 Protection Rating. It also has a lifespan of over 100,000 hours. The Linear II is also CE, DLC, and ETL certified.



www.lightingoftomorrow.com

1-800-538-4446